



# CLAYSTONE

TECHNICAL SPECIFICATION



# This Range

A versatile collection of porcelain tiles, suitable for interior applications. Available in 9mm, offering a balance of elegance and durability.

## Sizes

1200 x 600 x 9.5mm rectified natural



Heavy Footfall



Stairs



Interior



Wet Areas

## Colours



Fog



Ash



Sand



Fawn



Dove

# Technical Details

<b>Technical Features</b>	<b>Test Method</b>	<b>Required Values</b>	<b>Average Values</b>
Water Absorption	ISO 10545-3	$\leq 0.5\%$	Compliant
Modulus of Rupture	ISO 10545-4	$R \geq 35 \text{ N/mm}^2$	Compliant
Breaking strength	ISO 10545-4	$S \geq 1300 \text{ N}$	Compliant
Thermal Shock Resistance	10545-9	Required	Compliant
Frost resistance	10545-12	Resistant	Compliant
Chemical resistance	ISO 10545-13	MINIMUM GB	GA



**-Claystone Dove  
(Floor & Wall)**



**-Claystone Dove  
(Wall)**



**-Claystone Ash  
(Floor)**



**-Claystone Ash  
(Floor)**



**-Claystone Sand  
(Floor)**



**-Claystone Fawn  
(Floor & Wall)**



**-Claystone Fog  
(Floor)**



**-Claystone Fawn  
(Floor)**



KEYSTONE

204 Duggins Lane, Tile Hill, Coventry,  
CV4 9GP  
02475 092 859  
[www.keystoneco.co.uk](http://www.keystoneco.co.uk)

