



CONCRETE

TECHNICAL SPECIFICATION



This Range

A versatile collection of porcelain tiles, suitable for both interior and exterior applications. Available in 9mm and 20mm thickness, offering a balance of elegance and durability.

Sizes

1200 x 600 x 20mm rectified grip
1200 x 600 x 9mm rectified natural
800 x 800 x 9mm rectified natural
600 x 600 x 9mm rectified natural
600 x 300 x 9mm rectified natural



Heavy Footfall



Stairs



Interior



Exterior



Wet Areas



Pool Edging

Colours



Latte



Grigio



Sabd

Technical Details

Technical Features	Test Method	Required Values	Average Values
Water Absorption	ISO 10545-3	$\leq 0.5\%$	Compliant
Modulus of Rupture	ISO 10545-4	$R \geq 35 \text{ N/mm}^2$	Compliant
Breaking strength	ISO 10545-4	$S \geq 1300 \text{ N}$	Compliant
Thermal Shock Resistance	10545-9	Required	Compliant
Frost resistance	10545-12	Resistant	Compliant
Chemical resistance	ISO 10545-13	MINIMUM GB	GA



**-Concrete Grigio
Outdoor
(Floor)**



**-Concrete Sand
(Floor)**



**-Concrete Grigio
(Floor)**



**-Concrete Sand
(Floor)**



**-Concrete Latte
(Floor)**



**-Concrete Latte
(Floor)**



KEYSTONE

204 Duggins Lane, Tile Hill, Coventry,
CV4 9GP
02475 092 859
www.keystoneco.co.uk

