



DEIGHTON

TECHNICAL SPECIFICATION



This Range

A versatile collection of porcelain tiles, suitable for both interior and exterior applications.
Available in 8.5mm and 20mm thickness, offering a balance of elegance and durability.

Sizes

1200 x 600 x 20mm rectified grip
1200 x 600 x 8.5mm rectified natural
600 x 600 x 8.5mm rectified natural
600 x 300 x 8.5mm rectified natural



Heavy Footfall



Stairs



Interior



Exterior



Wet Areas



Pool Edging

Colours



Ashen



Shale



Sand



Gravel

Technical Details

Technical Features	Test Method	Required Values	Average Values
Water Absorption	ISO 10545-3	$\leq 0.5\%$	conforms to standard
Modulus of Rupture	ISO 10545-4	$\geq 35 \text{ N/mm}^2$	conforms to standard
Breaking strength	ISO 10545-4	$\geq 1300 \text{ N}$	conforms to standard
Slip Resistance	EN 16165 an.B	Stated Value	R10 , R11
	ANSI A326.3	Stated Value	>0.42
	B.C.R.A. Rep. CEC/81	Stated Value	conforms to standard
	EN 16165 an.C	Stated Value	conforms to standard
Thermal Shock Resistance	10545-9	Required	Resistant
Frost resistance	10545-12	Required	Resistant
Chemical resistance	ISO 10545-13	Stated Value	LA - HA
Household chemicals resistance	ISO 10545-13	group B minimum	conforms to standard



-Deighton Ashen
(Floor & Wall)



-Deighton Shale
(Kitchen Wall)



**-Deighton Shale
(Outdoor Floor)**



**-Deighton Gravel
(Pool)**



**-Deighton Gravel
(Living Room)**



**-Deighton Sand
(Bathroom)**



**-Deighton Ashen
(Floor)**



**-Deighton Shale
(Floor & Wall)**



-Deighton Shale



-Deighton Sand
(Outdoor)



KEYSTONE

204 Duggins Lane, Tile Hill, Coventry,
CV4 9GP

02475 092 859

www.keystoneco.co.uk

