



ESSENCE

TECHNICAL SPECIFICATION



This Range

A versatile collection of porcelain tiles, suitable for both interior and exterior applications. Available in 9mm, 9.5mm, and 20mm(60x60 grip), offering a balance of elegance and durability.

Sizes

1200 x 600 x 9.5mm rectified natural
800 x 800 x 9mm rectified natural
800 x 400 x 9mm rectified natural
600 x 600 x 9mm rectified natural
600 x 300 x 9mm rectified natural
300 x 300 x 9mm rectified natural
300 x 100 x 9mm rectified natural

1200 x 600 x 9.5mm rectified grip
600 x 600 x 9mm rectified grip
600 x 600 x 20mm rectified grip
600 x 300 x 9mm rectified grip
300 x 300 x 9mm rectified grip



Heavy Footfall



Stairs




Interior



Exterior



Wet Areas



Pool Edging

Colours



Sand



White



Anthracite



Graphite

Technical Details

Technical Features	Test Method	Required Values	Average Values
Water Absorption	ISO 10545-3	$\leq 0.5\%$	Conforms to standard
Modulus of Rupture	ISO 10545-4	$\geq 35 \text{ N/mm}^2$	Conforms to standard
Breaking strength	ISO 10545-4	$\geq 1300 \text{ N}$	Conforms to standard
Thermal shock resistance	ISO 10545-9	Required	Resistant
Frost resistance	ISO 10545-12	As indicated by manufacturer	Resistant
Chemical resistance	ISO 10545-13	Min Class B	Resistant



-Essence Graphite(Floor)
-Essence Anthracite(Wall)



-Essence Sand
(Floor)



-Essence Sand(Floor)
-Essence White(Wall)



-Essence Graphite
(Floor)



**-Essence Graphite
(Floor)**



**-Essence White
(Floor)**



-Essence White (Floor)



**-Essence Anthracite
(Floor)**



KEYSTONE

204 Duggins Lane, Tile Hill, Coventry,
CV4 9GP

02475 092 859

www.keystoneco.co.uk

