



FOSSIL


TECHNICAL SPECIFICATION



Fossil

Beautifiul range of porcelain tiles, suitable for interiors and exteriors. From inside to out tiles, in 9mm thickness


Suitable for:



Exterior



Heavy Footfall



Pool Edging



Stairs

Sizes

1200 x 600 x 9mm rectified natural
1200 x 600 x 9mm rectified grip
600 x 600 x 9mm rectified natural
600 x 600 x 9mm rectified grip
600 x 300 x 9mm rectified natural
600 x 300 x 9mm rectified grip
300 x 300 x 9mm rectified natural
300 x 300 x 9mm rectified grip
300 x 100 x 9mm rectified natural
mosaic 300 x 300 (5x5) x 9mm rectified natural
skirting 600 x 60 x 9mm rectified natural

Colours



Chalk



Cream



Graphite



Griege

Technical Details - 9mm

Technical Features	Test Method	Required Values	Average Values
Water Absorption	ISO 10545-3	$\leq 0,5\%$	0,2%
Flexion Resistance	ISO 10545-4	$\geq 35 \text{ N/mm}^2$	Compliant
Linear Thermal Expansion	ISO 10545-8	Declared value	$\alpha = 6,7 \times 10^{-6} / ^\circ\text{C}$
Stain Resistance	ISO 10545-14	Classe / Class 3 Min.	Complying
Chemical Resistance (*)	ISO 10545-13	Declared Value	Compliant
Frost Resistance	ISO 10545-12	Compliant	No damage
Slip Resistance	BS 7976:2002	Nat R10, Grip R11 A,B&C Pendulum Grip +/- 36 wet	Compliant
Thickness	ISO 10545-2	+/- 0.5mm	Compliant
Recommended Joint Width		Rectified	2mm

(*) Excluding hydrofluoric acid and its derivatives. (**) The width of grout joints must be established by the installation supervisor, unless grout widths are regulated by national laying standards.

Packaging Details

Size	Pz/Box	Kg/Box	Mq/Box	Box/Pal	Kg/Pal	Mq/Pal
1200 x 600 x 9mm rectified	2	28.4	1.44	36	1022.4	51.84
600 x 600 x 9mm rectified	3	21.3	1.08	40	852	43.2
600 x 300 x 9mm rectified	6	21	1.08	48	1008	51.84
300 x 300 x 9mm rectified	12	21	1.08	48	1008	51.84
300 x 100	32	19.3	.96	36	694.8	34.56



Chalk

Cream





Graphite

Greige





204 Duggins Lane, Tile Hill, Coventry,
CV4 9GP
02475 092 859
www.keystoneco.co.uk



