



Marbelo

TECHNICAL SPECIFICATION



KEYSTONE

This Range

A versatile collection of porcelain tiles with a marble effect, suitable for interior applications.
Available in 10mm thickness, offering a balance of elegance and durability.

Sizes

1200 x 600 x 10mm rectified polished



Heavy Footfall



Interior

Colours



Carrara



Calacatta




Staturio



Beige



Grey



Onix

Technical Details

Technical Features	Test Method	Required Values	Average Values
Water Absorption	ISO 10545-3	$\leq 0.5\%$	$\leq 0,5\%$
Modulus of Rupture	ISO 10545-4	$\geq 35 \text{ N/mm}^2$	conforms to standard
Breaking strength	ISO 10545-4	-	-
Thermal Shock Resistance	10545-9	Required	Resistant
Frost resistance	10545-12	Required	Resistant
Chemical resistance	ISO 10545-13	Required	conforms to standard
Slip resistance	DIN EN 16165	Basing on the environment or on the working area or on the wet-loaded barefoot areas	$> 0,4$



**-Marbelo Calacatta
(Wall)**



**-Marbelo Statuario
(Floor)**



**-Marbelo Beige
(Floor)**



**-Marbelo Grey
(Floor)**



**-Marbelo Carrara
(Floor)**



**-Marbelo Onix
(Floor)**



**-Marbelo Carrara
(Floor)**



**-Marbelo Calacatta
(Floor)**



KEYSTONE

204 Duggins Lane, Tile Hill, Coventry,
CV4 9GP

02475 092 859

www.keystoneco.co.uk

