



SAND OUTDOOR PORCELAIN

TECHNICAL SPECIFICATION



This Range

A versatile collection of porcelain tiles, suitable for exterior applications. Available in 20mm , offering a balance of elegance and durability.

Sizes

800 x 800 x 20mm rectified grip
600 x 600 x 20mm rectified grip



Heavy Footfall



Stairs



Exterior




Wet Areas




Pool Edging


Colours



Anthracite



Grigio



Beige

Technical Details

Technical Features	Test Method	Required Values	Average Values
Water Absorption	ISO 10545-3	≤ 0.5%	Compliant
Modulus of Rupture	ISO 10545-4	Conforms to standard	Conforms to standard
Breaking strength	ISO 10545-4	Conforms to standard	Conforms to standard
Thermal Shock Resistance	ISO 10545-9	Required	Compliant
Frost resistance	ISO 10545-12	Resistant	Compliant
Chemical resistance	ISO 10545-13	Resistant	Compliant



**-Sand Anthracite
(Floor)**



**-Sand Beige
(Floor)**



**-Sand Anthracite
(Floor)**



**-Sand Grigio
(Floor)**



**-Sand Beige
(Floor)**



**-Sand Grigio
(Floor)**



KEYSTONE

204 Duggins Lane, Tile Hill, Coventry,
CV4 9GP

02475 092 859

www.keystoneco.co.uk

