



WAINWRIGHT

TECHNICAL SPECIFICATION



This Range

A versatile collection of porcelain tile, suitable for both interior and exterior applications. Available in 9.5mm and 12mm thickness, offering a balance of elegance and durability.

Sizes

1200 x 600 x 20mm rectified grip
1200 x 600 x 9.5mm rectified natural
900 x 900 x 9.5mm rectified natural
600 x 600 x 9.5mm rectified natural
600 x 300 x 9.5 rectified natural

600 x 600 x 9.5mm rectified grip
600 x 300 x 9.5mm rectified grip
404 x 200 x 12mm grip
302 x 200 x 12mm grip
200 x 200 x 12mm grip



Heavy Footfall



Stairs



Interior



Exterior



Wet Areas



Pool Edging

Colours



Helvellyn



Blencathra



Bowfell



Glaramara



Scafell

Technical Details

Technical Features	Test Method	Required Values	Average Values
Water Absorption	ISO 10545-3	$\leq 0.5\%$	$\leq 0.5\%$
Modulus of Rupture	ISO 10545-4	$\geq 35 \text{ N/mm}^2$	50 N/mm ²
Breaking strength	ISO 10545-4	$\geq 1300 \text{ N}$	2.200 N 9,5 mm 3.500 N 12 mm 13.600 N 20 mm
Linear Thermal Expansion	ISO 10545-48	No provision	$\alpha \leq 7 \times 10^{-6} \text{ }^{\circ}\text{C}^{-1}$
Frost resistance	ISO 10545-12	As indicated by manufacturer	Resistant
Chemical resistance	ISO 10545-13	As indicated by manufacturer	Resistant



-Mortar Grey
(Floor)



-Mortar Grey
(Floor)



**-Mortar Grey
(Floor)**



**-Mortar Grey
(Floor)**



-Mortar Grey
(Floor)



-Mortar Grey
(Floor)



**-Mortar Grey
(Floor)**



**-Mortar Grey
(Floor)**



-Mortar Grey
(Floor)



-Mortar Grey
(Floor)



KEYSTONE

204 Duggins Lane, Tile Hill, Coventry,
CV4 9GP

02475 092 859

www.keystoneco.co.uk

